



PSR-15A NEO

Portable Powered
Speaker System

Key Features:

- High Impact Molded Polypropylene Enclosure
- Dynamic Switch Mode Power Supply
- High Efficient Class D Amplifier
- Neodymium LF Transducer
- 1.4" Voice Coil, 1" Exit Titanium Compression Driver
- 80°×60° Coverage Pattern
- Smooth Response With High Power Handling Capacity (Long Term/Max), 121dB/124dB
- 5 Integral Suspension Points
- Complete Mounting Solutions



General Description and Applications:

W-Audio sets new standards in active loudspeakers for musicians, DJ's and any audio professional looking for a compact quality solution to the world's oldest audio problem; accurate reproduction. The PSR series offers superior sound and has features that until now have only been found on more expensive professional equipment. Design and build quality is not limited to the audio performance. Safe and easy installation is guaranteed by multiple rigging points and functional casing design gives true multifunction capability without compromise.

The PSR Range feature VariFlare; a rotational top end horn flare. This unique feature allows an installer or audio specialist to really tailor the HF dispersion to the situation needed making the PSR range ideal as a foldback monitor or horizontal installation cabinet. Built to last the W-Audio passive electronics contain custom filter circuitry designed to optimize the box's sonic performance and help protect the driver components. With quality high powered components, advanced electronics and sturdy box design, the PSR series will outlast even the toughest user environments yet still deliver first class audio reproduction.

Technical Specification:


Freq.Range(-10dB):	55Hz~20kHz
Freq.Response(-3dB):	65Hz~18kHz
Rec.Hipass Frequency:	40Hz
Max Calculated SPL:	125dB
Horizontal Coverage:	80°
Vertical Coverage:	60°
Amplifier Power LF:	300W
Amplifier Power HF:	50W
Crossover Frequency:	2.2kHz
Loop/Mix Out:	XLR/M,Balanced
AC Input:	110/220 V,AC,50/60Hz,350 Watts
Dim (H×W×D):	740mm×475mm×400mm
Net Weight:	21Kg
Shipping Weight:	26Kg




PSR-15A NEO

Portable Powered Speaker System

Frequency Response



Block Diagram



Dimension Drawings

